

40M IR VARI-FOCAL BULLET CAMERA

I4-390IPAVF



1/3" CMOS Sensor
2 Mega-Pixel
True Day & Night (IR Cut Removable)
H.264+ Compression
0 Lux (IR On) Min. Illumination

ONVIF
Digital WDR
3D Noise Reduction
Motion Detection and Privacy Masking
2.8-12mm Vari-Focal Lens

40m IR Illumination
PoE Support
1 Way Audio
IP 66 Protection

Specifications

Camera	Video	Model	I4-390IPAVF
		Image Sensor	1/3" CMOS
		Effective Pixels	1920×1080
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	1-25/30
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	G711A/U
		Communication	One Way Audio
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto / Manual) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	Digital WDR
		Noise Reduction	3D-DNR / ROI
		Image Orientation	Mirror/Flip/Vertical Mode
		Privacy Zone	Yes
		Motion Detection	Yes
	Compression	Video Compression	H.264+
		Resolution	1080P (1920×1080), 720P (1280×720), VGA, QVGA
		Multi-stream	1920×1080 (1~30fps) / 1280×720 (1~30fps) / 1280×720 (1~30fps) / 640×480 (1~30fps) / 320×240 (1~30fps)
		Bit rate	128Kbps ~ 6Mbps
		Encode Mode	VBR/CBR
		Image Quality	Five levels under VBR; Free adjustment under CBR

Housing	IR Distance	40m (48 IR LED)
	Lens	2.8-12mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis
	Dimensions	Φ109mm×284mm
Connectivity	Weight(gross)	1115g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Mic Connectivity	1Ch Input
	SD Card	No
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS Control Software
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
Others	Power Supply	DC12V/~600mA / PoE/~8.5W
	Work Environment	-30 C ~50 C , 10%~90% Humidity

