



Key Features

- On-Screen-Display (OSD) & Cascade Chain functions
- Intuitive on-screen menus for quick and efficient navigation
- Three level password access: Administrator, User and Viewer
- Supports cascade chaining for control of up to 4096 PCs¹
- PS/2 or USB keyboard emulation for error-free boot up
- Supports hot-plugging
- Supports 3 switching methods:
 - Front Panel Button
 - Hot-Keys on a PS/2 keyboard
 - OSD Menu (On-Screen-Display)
- Supports Auto-Scan function
- Front panel LEDs for PC and/or server status indication
- Supports monitor resolutions up to 2048 x 1536
- Audible feedback when switching
- Supports Windows, Linux, Mac OS9/OSX, and Sun Microsystems Operating Systems
- Fully compliant with USB 1.1/ 2.0 specifications
- Rack mountable in 19" system rack (1U)

8/16-Port PS2/USB Combo KVM Switch

The D-Link PS2/USB Combo KVM Switch is a high-performance local remote management solution designed for small to medium server rooms that require access and control of multiple servers. Additional KVM switches can be cascaded allowing control of up to 512 (KVM-440) or 4096 (KVM-450) servers from a single console. The switch supports both USB and PS/2 platform servers and is fully compatible with all the major operating systems.

Versatile Management

The KVM-440/450 allows you to control and monitor up to 8 or 16 PS/2 and USB platform servers from a single console. Instantly toggle between multiple computers using the front panel buttons, keyboard hot-keys, or On-screen Display (OSD) menu. The OSD menu allows you to assign names to each connected PCs, providing easy and efficient server navigation. With a convenient Auto-Scan function, the KVM-440/450 automatically switch between multiple computers sequentially at preset intervals. Additionally, the front panel LEDs permit easy workstation/ server status monitoring.

Convenient Installation

The sturdy metal chassis is mountable in a standard 19" system rack. Multiple KVM switches can be cascaded together up to three levels deep to expand your KVM configuration; cascaded units require no special configuration for easy installation. A PS/2 or USB keyboard is emulated on each terminal allowing all connected computers to successfully boot up without keyboard errors. Hot-plug compliant allows you to add or disconnect computers without turning your PCs off. Finally, upgradable firmware ensures compatibility with the latest hardware.

Additional Features

The KVM-440/450 supports VGA, SVGA, and MultiSync monitors at resolutions of up to 2048 x 1536 with refresh rates of up to 65 Hz. With the password protection function, this KVM switch allows you to specify the name and password for an administrator and up to 3 users to prevent unauthorized users from accessing the KVM Switch. Reliable, convenient and scalable, the D-Link PS2/USB Combo KVM Switch is an ideal local remote management solution for your data center.

KVM-440/450 8/16-Port PS2/USB Combo KVM Switch



Technical Specifications		KVM-440	KVM-450
Computer Connections	Single KVM	8	16
	Cascade Chaining	Up to 512	Up to 4096
Selection Method		<ul style="list-style-type: none"> Switch Button, Hot-Keys (PS/2 Keyboard), and On-Screen-Display (OSD) 	
LEDs		<ul style="list-style-type: none"> Red for PC Selected Green for PC On-Line/Ready 	
PC Connectors		8 x HDB-15 female	16 x HDB-15 female
		<ul style="list-style-type: none"> Support both PS/2 and USB platform servers 	
Console Ports	Keyboard	<ul style="list-style-type: none"> 1 x 6 pin mini-DIN female 	
	Mouse	<ul style="list-style-type: none"> 1 x 6 pin mini-DIN female 	
	Video	<ul style="list-style-type: none"> 1 x HDB-15 female 	
Firmware Upgrade Port		<ul style="list-style-type: none"> Mini USB 	
Auto-Scan Interval		<ul style="list-style-type: none"> 5 to 90 seconds 	
Video Resolution		<ul style="list-style-type: none"> Max. resolution up to 2048 x 1536 @ 65 Hz 	
Hot-swappable		<ul style="list-style-type: none"> Yes 	
Operating Systems Supported		<ul style="list-style-type: none"> Windows 98SE/ME/2000/2003/2008/XP/Vista/7, Linux, Mac OS 9/OS X and Sun Microsystems 	
Power		<ul style="list-style-type: none"> 5V, 2A 	
Housing Material		<ul style="list-style-type: none"> Metal 	
Operating Temperature		<ul style="list-style-type: none"> 32°-122°F (0-50°C) 	
Humidity		<ul style="list-style-type: none"> 0%-80% Relative Humidity 	
Certifications		<ul style="list-style-type: none"> FCC, CE, C-Tick, IC, CSA 	
Dimensions (L x W x H)		<ul style="list-style-type: none"> 17.3 x 6.1 x 1.5 inches (44 x 15.7 x 4.5 cm) 	
Weight		3.9 lbs (1750 g)	4.2 lbs (1900 g)
Warranty		<ul style="list-style-type: none"> 1 Year Limited² 	

Ordering Information

<i>Part Number</i>	<i>Description</i>
KVM-440	8-Port PS2/USB Combo KVM Switch
KVM-450	16-Port PS2/USB Combo KVM Switch

¹ Cascade chaining for control of up to 512 (KVM-440) or 4096 (KVM-450) servers from a single console.

² 1-Year Limited Warranty available only in the USA and Canada.

Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted on the package. See inside package for warranty details.

business

For more information

D-Link Systems, Inc. | 17595 Mt. Herrmann Street | Fountain Valley, CA 92708 | 800.326.1688 | dlink.com