


IR MOTORIZED VF DOME CAMERA

DI-340IP5MVF



1/3" CMOS Sensor
4 Mega-Pixel
True Day & Night (IR Cut Removable)
H.265 (HEVC) Compression
0 Lux (IR On) Min. Illumination
ONVIF

True WDR / BLC / HLC
3D Noise Reduction
Motion Detection and Privacy Masking
3.3-12mm Motorized Lens with Auto-Focus
25m IR Illumination
PoE Support

1 Way Audio
CVBS
IP 66 Protection

Specifications

Camera	Video	Model	DI-340IP5MVF
		Image Sensor	1/3" CMOS
		Effective Pixels	2688x1520
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	1-25/30 (With True-WDR)
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	True WDR / BLC / HLC / ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
Compression		Video Compression	H.265 / H.264
	Resolution	4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240	
	Multi-stream	4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS)	
	Bit rate	64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264	
	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	25m (2 High Power IR LED)
	Lens	3.3-12mm Motorized with Auto-Focus
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis Wall Bracket
	Dimensions	Ø120mm×100mm
Connectivity	Weight(gross)	400g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS (RCa1)
	Mic Connectivity	1Ch Input
	SD Card	No
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
Others	Power Supply	DC12V/~280mA / PoE~4W
	Work Environment	-30 C ~50 C, 10%~90% Humidity

