


30M IR FIXED LENS BULLET CAMERA

I3-340IP536



1/3" CMOS Sensor
4 Mega-Pixel
True Day & Night (IR Cut Removable)
H.265 (HEVC) Compression
0 Lux (IR On) Min. Illumination

ONVIF
True WDR / BLC / HLC
3D Noise Reduction
Motion Detection and Privacy Masking
3.6mm Mega-Pixel Lens

30m IR Illumination
PoE Support
1 Way Audio
CVBS
IP 66 Protection

Specifications

Camera	Video	Model	I3-340IP536
		Image Sensor	1/3" CMOS
		Effective Pixels	2688x1520
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	Standard: 1-25/30 (True-WDR), HFR*: 1-50/60 (Max. 1080P & D-WDR)
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto)
		Image Enhancement	Sharpness, Saturation, Brightness & Contrast Adjustable
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
Compression	Video Compression		H.265 / H.264
	Resolution		4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240
	Multi-stream		4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS / 1~50/60FPS with HFR*)
	Bit rate		64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264
	Encode Mode		VBR/CBR
	Image Quality		Five levels under VBR; Free adjustment under CBR

*HFR (High Frame Rate) must be supported by the NVR in order to work properly.

Housing	IR Distance	30m (42 IR LED)
	Lens	3.6mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis Wall Bracket
	Dimensions	Φ87mm×219mm
Connectivity	Weight(gross)	635g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS (BNCx1)
	Mic Connectivity	1Ch Input
	SD Card	No
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
Others	Power Supply	DC12V/~500mA / PoE/~6.5W
	Work Environment	-30 C ~50 C, 10%~90% Humidity

